LIGHTWARE

CAB-USBC-T400B

SKU: 13740023

4m (13.12ft) Full-Featured USB-C cable for USB3.2 Gen 1x2, 4K60 Video and 60W/3A Charging

The CAB-USBC-T400B is a premium, 4-meter USB Type-C to Type-C passive copper cable designed to deliver high performance connectivity in meeting rooms, offices and auditoriums.





Details

This full-featured USB-C cable transmits **USB 3.2 Gen 1x2 (10Gbps)** data, USB 2.0, DisplayPort Alternate Mode video, and up to **60W USB Power Delivery (PD)** to keep presenter laptops charged over a single, short-distance connection. The cable **adds tiers neither** to USB2 nor to USB3 topology. Both the **2-lane and 4-lane** DP Alt mode signals are handled.

The cable proved itself to work with great efficiency with our USB-C capable **Taurus UCX** as well as with various source devices. The **soft-touch TPE** outer jacket and **gold-plated connectors** provide a premium look and feel to this 4-meter cable.

The cable has been **fully tested and optimized** for out-of-the-box reliability with the Lightware Taurus product family and a wide range of global source devices.

Premium Companion Accessories (sold separately)

C-PopUp-20 Enclosure: A sleek, desk-mounted pop-up interface that hides cables beneath the table surface or podium when not in use, preserving clean, premium executive aesthetics.

C-LOCK Cable flange: This accessory enhances safety and reliability by offering a 2-point securing for connected USB-C cables.

Features

- **Full-Featured USB-C**
- **4m**
- **60W/3A Charging**

Specifications

Interface	Connectors	2 × USB Type-C male
Technical parameters	Maximum data speed	10 Gbps (5 Gbps/lane)
	Data type	USB 3.2 Gen 1×2, USB 2.0, USB 1.1
	eMarker chip	Yes
	Displayport alternate mode	Yes, HBR2, 2-4-lane
	Video format	Up to 4096×2160@60Hz at RGB 4:4:4 and 5120×2160@30Hz at RGB 4:4:4
	Number of USB3 tier	0
	Number of USB2 tier	0
	Rated voltage	20 V
	Rated current	3 A
	Operating temperature	–10 °C to +60 °C
	Flammability	VW-1
Physical parameters	Length	4 m
	Cable diameter	5.3 mm
	Jacket material	TPE
	Wire material	Copper, 28 AWG
	Mold material	PVC
	Pin coating	Gold-plated
	Bending radius	21.2 mm
	Pulling force	4 kg
	Compliance	RoHS
	Color	Black

Connector Drawing

