



4m (13.12ft) Full-featured USB-C cable for USB3.2 Gen 1x2, 4K60 Video and 100W/5A Charging, Microcoax technology



Details

This Type-C to Type-C USB cable offers data speeds up to 10Gbps and allows users to connect their laptop or other devices to Lightware's USB-C compatible extenders and switchers. The cable's length of 4m is ideal for most meeting rooms and presenter's desk applications.

The cable proved itself to work with great efficiency with our USB-C capable **Taurus UCX/TPX/TPN family** as well as with various source devices. Its reliability, build quality, and technical parameters make this accessory our number-one choice for projects involving USB-C connectivity.

The Microcoax technology makes it possible to send video signals over greater distances with a thinner cable that, combined with the TPE outer jacket, results in more flexible cable that is also less sensitive to noise.

Features

- **4m length** for comfortable use
- **100Watt / 5A charging and eMarker**
Fast Charging of Laptops, tablets and phones
- **USB 3.2 Gen 1x2 10Gbps "SuperSpeed"**
4K Webcam, SSD storage
- **Supporting peripherals via USB 2.0 up to 480 Mbps**
Mouse, Keyboard, Thumb Drive, Speakerphone and Webcam
- **4 Lane DisplayPort Alt mode**
4K60FPS Video and Audio
- **Robust TPE jacket for durable use**
- **Connector dimensions according to standard.**
No bulky repeaters along the cable
- **10.000 Mating Cycle**
- **75µ Gold-plated contacts**

Specifications

Interface	Connectors	2 × USB Type-C male
Technical parameters	Maximum data speed	10 Gbps (5 Gbps/lane)
	Data type	USB 3.2 Gen 1×2, USB 2.0, USB 1.1
	eMarker chip	Yes
	Displayport alternate mode	Yes, HBR2, 2-4-lane
	Video format	Up to 4096×2160@60Hz at RGB 4:4:4 and 5120×2160@30Hz at RGB 4:4:4
	Number of USB3 tier	0
	Number of USB2 tier	0
	Rated voltage	20 V
	Rated current	5 A
	Operating temperature	-10 °C to +60 °C
	Flammability	TBD
Physical parameters	Length	4 m
	Cable diameter	5.9 mm
	Jacket material	TPE
	Wire material	Copper, 28 AWG
	Mold material	PVC
	Pin coating	Gold-plated
	Bending radius	21.2 mm
	Pulling force	4 kg
	Compliance	TBD
	Color	Black

Connector Drawing

