



ARCHITECTURAL AND ENGINEERING SPECIFICATION

PRODUCT: HDMI-TPX-RX107AU2K-SR

FUNCTIONAL OVERVIEW

The HDMI-TPX-RX107AU2K-SR is an SDVoE-based TPX receiver extender with integrated scaling and USB 2.0 (Icron) KVM/USB extension capability. It receives an HDMI 2.0 compliant AV stream and control signals over a 10GBase-T TPX (RJ45) link and outputs HDMI up to 4K60 4:4:4 with ultra-low latency (under 8 ms). The built-in scaler supports multiple display modes (including fast switching). The unit supports HDCP 2.3 and provides Ethernet and RS-232 interfaces for control and integration.

VIDEO INPUT AND OUTPUT

- Video input (TPX / SDVoE)
 - Connector: RJ45 female (TPX input)
 - Data rate: 10GBase-T
 - Compliance: SDVoE
 - HDCP compliance: HDCP 2.3
 - Color space: RGB, YCbCr
 - Video latency: 0 frame (five lines / under 8 ms)
 - Compression ratio: 1.4 : 1 (applied only if AV signal exceeds HDMI 1.4 bandwidth)
 - Supported resolutions at 8 bits/color: up to 4096x2160@60Hz (4:4:4) or up to 3840x2160@60Hz (4:4:4)
 - Transferred signals: Video, Audio, RS-232, Infrared, Ethernet, CEC
- Video output (HDMI)
 - Connector: 19-pole HDMI Type A receptacle
 - Standard: DVI 1.0, HDMI 1.4, HDMI 2.0
 - Supported resolutions at 8 bits/color: up to 4096x2160@60Hz (4:4:4) or up to 3840x2160@60Hz (4:4:4)
 - CEC support: Transparent
- Integrated scaler (receiver feature)
 - Available modes: genlock, genlock_scaling, fastswitch (default), wall, wall_fs
 - If scaler is enabled, HDMI output is always RGB 8 bit/channel

AUDIO CAPABILITIES

- HDMI embedded audio is received over TPX and output on HDMI
- Analog audio de-embedding via 5-pole Phoenix® analog audio output
 - Audio format: 2-channel PCM
 - Signal transmission: balanced
 - Sampling frequency: 48 kHz

POWERING

- Local power via 12V DC input (locking DC connector; supplied power: 12V DC, 2A)
- Remote power via TPX input using PoE PD (IEEE802.3af)

CONTROL

- Control network via 1GBase-T Ethernet (RJ45)
- Configuration/monitoring via BlueRiver AV Manager
- API control via TCI API (TCP/IP terminal connection) and REST API
- RS-232 control via 3-pole Phoenix® connector (bi-directional serial communication)
- USB (Icron) configuration and pairing control supported via SDVoE protocol when Icron control is enabled in SDVoE settings

GENERAL

- Dimensions: 138 W x 151.8 D x 26 H (mm)
- Mounting options compatibility (Size 1 device)
 - 1U High Rack Shelf: supported (3x)
 - UD Mounting Plate F120: supported (1x)
- LVD / electrical safety: EN 62368-1:2024
- Warranty period: 3 years
- Cooling: Passive



- Supplied accessories (receiver package)
 - Safety and Warranty Info; Quick Start Guide
 - TPX / OPTX series extender (device)
 - 12V DC adaptor with interchangeable plugs
 - Phoenix® Combicon 3-pole connector (RS-232)
 - Phoenix® Combicon 5-pole connector (analog audio)
- Packaging: the product has full paper / green packaging

DOCUMENT REVISION HISTORY

Document	Release Date	Changes	Checked by
v1	2026-07-27	Initial version	Tamas Forgacs