



ARCHITECTURAL AND ENGINEERING SPECIFICATION

PRODUCT: MX-FR17R

FUNCTIONAL OVERVIEW

Lightware's hybrid modular matrix routers allow building custom I/O sizes that meet the user's requirements. Different types of input and output boards give maximum flexibility for rental and installation signal transmission. The hybrid architecture allows signal routing between boards even if they have different connectors. Any input can be routed to any one or more outputs if the output interface is capable of transmitting the signal. Various input and output interface boards are available that can be mixed in the same frame without limitation.

I/O BOARD SPECIFICATION

- Rack height: 4U
- Max. input boards: 2
- Max. input ports: 17
- Max. output boards: 2
- Max. output ports: 17
- INFO: The maximum number of input and output ports includes the Test input and Preview output port of the MX-CPU2 processor board.

POWERING

- Power supply option: Swappable PSU
- Supported power source: 100-240 V AC; 50/60 Hz
- Power supply unit(s) type: MX-PSU-350
- Power consumption (max) of MX-FR17R: 210 W
- Heat dissipation: 1194 BTU/h
- AC power connector: IEC C14 receptacle

CONTROL

- Front Panel Control
- Lightware Device Controller (LDC)
- Built-in Website



- Ethernet Control (multiple simultaneous TCP/IP connections; simple ASCII based protocol)
- USB Control (front panel USB configuration port)
- RS-232 or RS-422 Control (simple ASCII-based protocol)
- MX-CPU2 control board is required to control the matrix frame

GENERAL

- Rack mount: Yes, 4U high
- Enclosure material: 1 mm steel
- Dimensions in mm: W482 x D300 x H176
- Dimensions in inch: W19.0 x D11.8 x H6.9
- Weight of the frame (with MX-CPU2 board): 11.7 kg (25.8 lbs)
- Rack mounting: standard rack unit installation using supplied rack mounting ears (fixed to the frame).
- Supplied accessories:
 - IEC power cable
 - RS-232 straight serial cable
 - Safety and Warranty Info; Quick Start Guide
- Safety / electrical class: Class I apparatus construction (protective earth required).
- Compliance: CE; Safety: EN 60065:2014, Class I.
- Warranty period: 3 years.
- Cooling / ventilation requirement: ensure enough free space around the appliance; do not cover the appliance; leave ventilation holes free; never block or bypass ventilators (if any).

DOCUMENT REVISION HISTORY

Document	Release Date	Changes	Checked by
v1	2026-08-19	Initial version	Tamas Forgacs